

VISCOSITY STANDARD:

Omega 612 Universal Lubrication & Hydraulic Oil has a highly stable viscosity standard. It remains constant throughout temperature fluctuations and retains its texture regardless of varied conditions.

ANTI-WEAR:

Omega 612 has a number of easily recognizable advantages over ordinary 'oil-can' oils used in the workshop. One such advantage is its special ability to resist wear. It contains special built-in wear inhibitors that actually surface-alloy the frictional area and prevent direct interfacial contact!

FOAM-INHIBITED:

Ordinary oils tend to aerate, causing an influx of oxygen into the equipment. Oxygen is the carrier of corrosive oxidation and oxidation causes equipment deterioration and, eventually, costly breakdown!

ANTI-MAGNETIC:

Omega 612 is anti-magnetic. It does not attract metallic dust and magnetic particles. Omega 612 actually forms a fine film 'skin' that keeps such contamination and dust out of the lubricant and, therefore, away from the interfacial areas.

NOTE:

Ordinary general-purpose workshop lubricants are often electro-statically based. They form a minor but destructive magnetic field which 'draws' airborne particles into the lubricant. This causes untold contamination problems as well as the formation of an abrasive fluid that is constantly fed into valuable equipment. The abrasion promotes wear. Wear requires replacement. Replacement needs time. Time costs money!

LONG LASTING:

Surface migration (moving off or away from the frictional interface) is a major characteristic of ordinary oils currently used in workshops and factories for general-purpose applications. Omega 612 however, contains special supplements designed to promote interface tenacity and actually hold the lubricant in position and prevent migration.

EXCELLENT BASE OIL:

The character of a good lubricant is measured by the type of base oil the manufacturers have used to produce it. Most oils are wax-based or they use easily solidified naphthenic-base oil, which are known to promote oxidation. Omega 612 is, however, only made from the finest base stocks available.

RAPID WATER SEPARATION:

Water is a combination of hydrogen and oxygen. Since oxygen is the major cause of oxidation, it is not unreasonable to suggest that water also causes oxidation. Ordinary oils however, have a tendency to emulsify with water and carry it through the system. This creates inner corrosion which, like cancer, does its damage away from visual checking capabilities. Omega 612 has built-in anti-emulsifiers which positively prevent water infusion.

HIGH E. P. PROFICIENCY:

Omega 612 easily tolerates excessive instantaneous loads frequently encountered during normal industrial use.



Copyright, All rights reserved. ITW PP & F Korea Limited reserves the right to modify or change this product for purposes of improving its performance characteristics.
 OPIM612-1
 Ver. 2.0
 Rev. 3.0

 Rev. Date: 15 May 2023
 Reference: CKL

OPERATION RANGE:

Omega 612 has a high viscosity index and a low pour point coupled with ideal operating spans to give quality results.

APPLICATIONS:

Omega 612 is ideally suited for:

Chain Drives,	Bearings,
Electric Motors,	Lathes,
Reciprocating Compressors,	Enclosed Gears,
Rotary Compressors,	Hydraulic Equipment,
Torque Converters,	'Poclain' Hydraulics

and complete lubrication of all factory equipment.

Omega 612 meets & exceeds the following specifications:

- GM LS-2
- MIL-H-17672
- AFNOR NF E 48-690, 691 filterability

TYPICAL DATA:

	ASTM			TEST RESULT		
TEST	TEST METHOD	SAE 5	SAE 10	SAE 20	SAE 30	SAE 40
ISO Viscosity Grade	D-2422	15	32	68	100	150
Appearance	Visual	Clear to light yellow				
Density, Kg/L @ 15°C	D-1298	0.843	0.867	0.870	0.872	0.882
Viscosity, cSt @ 40°C	D-445	15.0	32.0	68.0	100	150
Viscosity, cSt @100°C	D-445	3.5	5.4	8.7	11.3	14.8
Viscosity Index	D-2270	106	106	105	101	101
Flash Point, COC, °C(°F)	D-92	220	216	243	261	264
Pour Point, °C	D-97	-31	-21	-27	-27	-24
Aniline Point, °C	D-611	97	116	118	111	113
Foaming Characteristics -				•		
All Sequences, After Settling	D-892	Nil	Nil	Nil	Nil	Nil
Rust-Preventing Characte	ristics -			·		
Salt Water, 48 hrs.	D-665	Pass	Pass	Pass	Pass	Pass
Oxidation Characteristics	-					
TOST life, hours	D-943	>5000	>5000	>5000	>5000	>4000
Zinc % Mass	-	0.027	0.027	0.027	0.027	0.027

The characteristics given above are typical of current production only and slight batch to batch variations should be expected.



Copyright, All rights reserved. ITW PP & F Korea Limited reserves the right to modify or change this product for purposes of improving its performance characteristics.

OPIM612-2	Ver. 2.0	Rev. 3.0
Rev. Date: 15 May 2023		
Reference: CKL		



Product name:Omega 612Supersedes date:2019-08-20Product No.:

Page:	1/11
Last revised date:	2023-05-08
SDS-ID:	GB-EN/10.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING				
1.1. Product identifier				
Product name:	Omega 612			
<u>Container size:</u>	5 I, 20 I			
1.2. Relevant identified uses	of the substance or mixture ar	nd uses advised ag	<u>ainst</u>	
Application:	Hydraulic oil. Universal lubricant.			
1.3. Details of the supplier of	<u>the safety data sheet</u>			
Supplier:	EU importer:	Distributed by:	Trust Engineering Company	
			9 Abdel Hamid El Deeb Street Alexandria, 21613 Egypt T: +(20)3 5822779 T: +(20)10 1223554	
<u>Manufacturer:</u>	ITW PP & F Korea Limited 13th FI., Unit B, PAX Tower 609 Eonju-ro, Gangnam-Gu Seoul, Korea 06108		5 Ahmed Shaker Street Fourth Zone Nasr City, 11586 Egypt T:+(20)2 26909965 T: +(20)10 122355	
	Tel:+82-2-2088-3560 Fax:+82-2-513-3567 magna@magnagroup.com www.magnagroup.com		info@trustengineering-eg.com www.trustengineering-eg.com	
Further information can be obtained from:	magna@magnagroup.com			
1.4. Emergency telephone nu	umber			
Emergency telephone:	Call a Poison Center, emerg NHS: 111	gency number or d	octor/physician.	

Product name:	Omega 612	Page:	2/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP:

The product is classified: Skin Irrit. 2;H315

2.2. Label elements



Warning
Causes skin irritation.
Wash hands thoroughly after handling.
Wear protective gloves.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Dispose of contents/container in accordance with local regulations.
This product does not contain any PBT or vPvB substances.
Degreasing to skin. Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: mineral oil and additives.

All substances in the product are either registered or exempt from registration under REACH. Only classified substances above threshold limits or substances with an exposure limit are shown.

CLP:

<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
98-99	64742-54-7	265-157-1	-	Distillates (petroleum), hydrotreated heavy	Skin Irrit. 2;H315	L
Note	s:	L: DMSO <	< 3% (IP 346)			
Refe	rences:	The full text for all hazard statements is displayed in section 16.				

Product name:	Omega 612	Page:	3/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures		
Inhalation:	Move into fresh air and keep at rest. In case of persistent throat irritation or coughing or after inhalation of oil mist: Seek medical attention and bring along these instructions.	
Skin contact:	Remove contaminated clothing immediately and wash skin with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.	
Ingestion:	Immediately rinse mouth and drink 1-2 glasses of water. Keep person under observation. If uncomfortable: Transportation to hospital. Bring along these instructions.	
4.2. Most important symptoms and effects, both acute and delayed		

<u>Symptoms/effects:</u> See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

<u>Medical attention/treatments:</u> Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media:	Small fires: Extinguish with carbon dioxide or dry powder.
	Larger fires: Extinguish with foam, carbon dioxide or dry powder.
	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-	Selection of respiratory protection for fire fighting: follow the general fire
fighters:	precautions indicated in the workplace.

Product name:	Omega 612	Page:	4/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

<u>Personal precautions:</u> Avoid inhalation of oil mist and contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

6.2. Environmental precautions

Environmental precautions:	Do not discharge into drains, water courses or onto the ground.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up:	Absorb spillage with oil-absorbing material. Clean contaminated area with oil- removing material.

6.4. Reference to other sections

References:	For personal protection, see section 8.
	For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Observe good chemical hygiene practices. Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.	
Technical measures:	Use work methods which minimise oil mist production.	
Technical precautions:	When working with heated oil, mechanical ventilation may be required.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures for safe storage:	No special precautions.	
Storage conditions:	Store in tightly closed original container in a dry, cool and well-ventilated place. Protect against direct sunlight.	
7.3. Specific end use(s)		

Specific use(s): Not relevant.

Product name:	Omega 612	Page:	5/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No occupational exposure limit assigned.

8.2. Exposure controls

Engineering measures:	Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.
Personal protection:	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Respiratory equipment:	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.
Hand protection:	Wear protective gloves. Nitrile gloves are recommended. Thickness: > 0,3 mm; Breakthrough time: > 240 min. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.
Eye protection:	Risk of contact: Wear goggles/face shield.
Skin protection:	Wear apron or protective clothing in case of splashes.
Hygiene measures:	Wash hands after contact. Wash contaminated clothing before reuse.
Environmental Exposure Controls:	Not available.

Product name:	Omega 612	Page:	6/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties		
Physical state:	Liquid.	
<u>Colour:</u>	Transparent brown.	
<u>Odour:</u>	Mild / almost odourless.	
Odour threshold:	Not available.	
<u>pH:</u>	Not available.	
Melting point / freezing point:	Not available.	
Boiling point:	Not available.	
Flash point:	> 200 °C	
Evaporation rate:	Not available.	
Flammability (solid, gas):	Not applicable.	
Explosive limits	Not available.	
Vapour pressure:	Not available.	
Vapour density:	Not available.	
Relative density:	0,855 / 0,864 / 0,868 / 0,871	
<u>Solubility:</u>	insoluble in water	
Partition coefficient (n- octanol/water):	Not available.	
<u>Auto-ignition</u> temperature (°C):	Not available.	
Decomposition temperature (°C):	Not available.	
<u>Viscosity:</u>	15,4 / 32 / 68 / 100 / 140,7 mm²/s (40°C)	
Explosive properties:	Not available.	
Oxidising properties:	Not available.	
9.2. Other information		
<u>Other data:</u>	Not available.	

Product name:	Omega 612	Page:	7/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 10: STABILITY AND REACTIVITY		
10.1. Reactivity		
Reactivity:	Not reactive.	
10.2. Chemical stability		
<u>Stability:</u>	Stable under normal temperature conditions.	
10.3. Possibility of hazardous	reactions	
Hazardous Reactions:	None known.	
10.4. Conditions to avoid		
Conditions to avoid	Heat, sparks, flames.	
10.5. Incompatible materials		
Incompatible materials:	Strong oxidising substances.	
10.6. Hazardous decomposition products		
Hazardous decomposition products:	None in particular.	

Product name:	Omega 612	Page:	8/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicologi	cal effects
Acute Toxicity (Oral):	Based on available data, the classification criteria are not met.
Acute Toxicity (Dermal):	Based on available data, the classification criteria are not met.
Acute Toxicity (Inhalation):	Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation:	Causes skin irritation.
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.
<u>Respiratory or skin</u> sensitisation:	Based on available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	Based on available data, the classification criteria are not met.
STOT - Single exposure:	Based on available data, the classification criteria are not met.
STOT - Repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Inhalation:	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing.
Skin contact:	Degreasing. Prolonged or frequent contact may cause redness, itching, irritation, eczema, skin cracking and oil acne.
Eve contact:	Splashes may irritate.
Ingestion:	May irritate and cause malaise.
Specific effects:	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer. The harmful effects may increase in used oil.

11.2. Information on other hazards

Endocrine disrupting	The product does not contain any substance identified as having endocrine
properties:	disrupting properties.

Product name:	Omega 612	Page:	9/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 12: ECOLOGICAL INFORMATION

<u>12.1. Toxicity</u>		
Ecotoxicity:	There are no data on the ecotoxicity of this product. Oil spills are generally hazardous to the environment.	
	Distillates (petroleum), hydrotreated heavy LC50 (Oncorhynchus mykiss, 96 h): > 5000 mg/l EC50 (Daphnia magna, 48 Stunden): > 1000 mg/l EC50 (Scenedesmus subspicatus, 96h): > 1000 mg/l	
12.2. Persistence and degrad	ability	
<u>Degradability:</u>	The product is expected to be slowly biodegradable.	
12.3. Bioaccumulative potenti	al	
Bioaccumulative potential:	No data available on bioaccumulation.	
<u>12.4. Mobility in soil</u>		
Mobility:	No data available.	
12.5. Results of PBT and vPv	<u>B assessment</u>	
<u>PBT/vPvB:</u>	This product does not contain any PBT or vPvB substances.	
12.6. Endocrine disrupting pro	perties	
Endocrine disrupting properties:	The product does not contain any substance identified as having endocrine disrupting properties.	
	disrupting properties.	
12.7. Other adverse effects		
Other adverse effects:	None known.	
SECTION 13: DISPOSAL CONSIDERATIONS		
13.1. Waste treatment method	<u>a</u>	
Dispose of waste and residue hazardous waste.	s in accordance with local authority requirements. Waste is classified as	

Waste from residues: EWC-code: 13 01 10

<u>Contaminated packaging:</u> Dispose of contaminated packings as residue.

Product name:	Omega 612	Page:	10/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/AND/RID).

14.1. UN number

UN-No:

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

Class:

14.4. Packing group

<u>PG:</u>

14.5. Environmental hazards

Marine pollutant:

Environmentally Hazardous

substance:

14.6. Special precautions for user

Special precautions: Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Statutory Instruments, 2021 No. 904, CONSUMER PROTECTION ENVIRONMENTAL PROTECTION HEALTH AND SAFETY. The REACH etc. (Amendment) Regulations 2021. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019 No.
 720), as amended. EH40/2005, Workplace exposure limits 2005, with amendments. The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

CSA status:

No chemical safety assessment has been carried out.

Product name:	Omega 612	Page:	11/11
Supersedes date:	2019-08-20	Last revised date:	2023-05-08
Product No.:		SDS-ID:	GB-EN/10.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1, 2, 3, 4, 6, 7, 8, 9, 10, 11, 12, 13, 15, 16.

Omega Manufacturing Division 13th floor, Unit B, PAX Tower, 609 Eonju-ro, Gangnam-Gu, Seoul, Korea 06108 Tel : +82-2-2088-3560 Fax : +82-2-513-3567 Web site : www.magnagroup.com

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

Abbreviations and acronyms	
used in the safety data sheet:	CSA= Chemical Safety Assessment.
	EC50 = Effective Concentration 50%.
	LC50 = Lethal Concentration 50%.
	PBT = Persistent, Bioaccumulative and Toxic.
	vPvB = very Persistent and very Bioaccumulative.
Additional information:	Classification according to Regulation (EC) No. 1272/2008: Calculation method.
Wording of H-statements:	
H315	Causes skin irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.